

| Project:      |  |  |  |
|---------------|--|--|--|
| Fixture Type: |  |  |  |
| Location:     |  |  |  |
| Contact:      |  |  |  |

# **ONE-LIGHT FLUSH MOUNT**

Ceiling mounted • Damp location listed PROGRESS LED

Images:



P350024-020-30



## **Description:**

A tapered, square, linen finish glass diffuser is paired with an energy-efficient, high-performance LED source in this contemporary ceiling fixture.

# **Specifications:**

- · Antique Bronze (-020) (painted)
- · Steel Construction
- Etched White Linen glass diffuser
- LED Module is replaceable (part # 93074252)
- · Features a tapered square, linen finish glass diffuser
- · Diffuser is paired with an energy-efficient, high-performance LED source.
- · 2015 lumens 80.6 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Fixture covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016



#### **Performance:**

| Number of Modules      | 1                                   |  |  |
|------------------------|-------------------------------------|--|--|
| Input Power            | 25w                                 |  |  |
| Input Voltage          | 120 V                               |  |  |
| Input Frequency        | 60 Hz                               |  |  |
| Lumens/LPW (Source)    | 1770/70 (LM-82)                     |  |  |
| Lumens/LPW (Delivered) | 1442/58.1 (LM-79)                   |  |  |
| CCT                    | 3000 K                              |  |  |
| CRI                    | 90+                                 |  |  |
| Life (hours)           | 50,000 (L70/TM-21)                  |  |  |
| FCC                    | Meets FCC Title 47, Part 15 Class B |  |  |
| Min. Start Temp        | -30 °C                              |  |  |
| Max. Operating Temp    | 30° C                               |  |  |
| Warranty               | 5 year warranty                     |  |  |
| Labels                 | cCSAus Damp location listed         |  |  |
|                        | ENERGY STAR® qualified              |  |  |
|                        | Meets California Title 24 JA8-2016  |  |  |

### **Dimensions:**

Diameter: 11-1/2" Height: 4-7/8"

Glass

Width: 11-1/2" Height: 4-1/2"



# **ONE-LIGHT FLUSH MOUNT**

Ceiling mounted • Damp location listed PROGRESS LED



P350024-020-30

## **Dimming Notes:**

P350024 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Lutron Lumea LG-603PG

Leviton SureSlide 6672

Leviton SureSlide 6674

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Cooper Devine AL DAL06P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron Maestro MA-600

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.