

## LED CTC COMM

Flush-Mount Mounted • Damp Location Listed PROGRESS LED



### Description:

Close-to-ceiling, surface mount round with clean modern lines and white acrylic diffuser. LED light engine with 1184 delivered lumens at 3000K and 90+ CRI.

### Specifications:

- White acrylic Diffuser
- Urban Bronze finish.
- Steel construction.
- Dimmable to 10% brightness with many Forward and Reverse Phase dimmers.
- 3000k color temperature.
- TM-21 54,000 hour life.
- Meets California Title 24 - JA8 - 2016.
- 1,184 lumens (delivered).
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" recessed outlet box: 14 in W., 0.375 in ht., 14 in depth
- Ceiling pan
- 6 in of wire supplied

### Performance:

Number of Modules	1
Input Power	22 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,184/53.8 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	ETL Damp Location Listed ENERGY STAR® qualified Meets California Title 24 JA8-2016


# P7253-17430K9



### Dimensions:

Diameter: 14 in  
Height: 3-3/4 in

White acrylic Diffuser  
Width: 13 in  
Height: 3-1/2781 in



# P7253-17430K9

## Dimming Notes:

---

P7253-17430K9 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Lutron\_Nova T VTELV-300

Lutron\_Diva DVELV-300P

Lutron\_Diva DVCL-253P

Lutron\_Caseta Wireless

Leviton\_6681

Leviton\_SureSlide 6672

Leviton\_SureSlide 6674

Lutron\_Ariadni AYLV-600P

Lutron\_NTLV-600

Lutron\_Maestro MAELV-601

Leviton\_AWRMG-EAW

Lutron\_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.