

Project:

Fixture Type:

Location:

Contact:

Intrinsic

Recessed housing Mounted • Damp Location Listed PROGRESS LED



Description:

Intrinsic Collection 1-Light Satin White Modern Recessed LED Downlight

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- + 6 in of wire supplied

Performance:

Number of Modules	1
nput Power	8 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	750/93 (LM-79)
ССТ	2700 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cULus Damp Location Listed
	ENERGY STAR [®] qualified
	Meets California Title 24 JA8-2016





Dimensions:

Length: 7-11/16 in Diameter: 7-11/16 in Height: 3-15/16 in



Intrinsic

Recessed housing Mounted • Damp Location Listed PROGRESS LED



 $\mathsf{P800018}\text{-}\mathsf{O28}\text{-}\mathsf{CS}$ is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

aton AAL06	
aton SAL06P	
Devices IDEV009	
viton 6681	
viton IPI06-1LZ	
viton 6672	
viton 6674	
tron NTEVL-300	
itron DVELV-300P	
itron Caseta Wireless	
itron AYCL-153P	
itron SCL-153P	
itron TGCL-153-PH-WH	
itron MACL-153M	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P800018-028-CS