

Project:			
Fixture Type:			
Location:			
Contact:			

Linear Cloud

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Description:

26" LED Linear Cloud

Specifications:

- · White Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- 15.7479 in W., 3.25 in ht., 5.6299 in depth

Performance:

Number of Modules	1
Input Power	27 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,000/76 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	52000 (L70/TM-21)
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016





Dimensions:

Length: 26 in Width: 10-1/4 in Height: 3-1/4 in

White Acrylic Diffuser Length: 26 in Width: 10-1/4 in





Linear Cloud

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

P7278-3030K9

 $\ensuremath{\mathsf{P7278\text{-}3030K9}}$ is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.