

# LED Flush Mount

 Pendant/ceiling semi-flush mounted • Damp location listed **PROGRESS LED**


## Description:

Designed for both commercial and residential interiors, Apogee is an energy efficient, high performance LED fixture. All fixtures feature 120-277V input with standard dimming. Etched glass shade provides an even and pleasing light effect. Apogee is 3000K, 90+ CRI and meets California Title 24 - JA8 - 2016 standards and is ENERGY STAR rated and damp location listed. The Apogee Collection 15" LED Flush Mount is complimented by a Brushed Nickel finish.

## Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Etched Glass shade
- Semi-flush fixture convertible to hanging pendant with included hardware and instructions.
- Commercial-grade construction and performance.
- Features Brushed Nickel finish.
- Etched glass shade provides an even and pleasing light effect.
- Features 28.3-watt integrated LED to deliver energy savings and reduce long-term maintenance costs.
- 120-277V operation, 0-10V compatible dimming.
- 3000K color temperature, 90CRI.
- 1660 lm, 59.5 Lum/Watt. (delivered)
- ENERGY STAR certified.
- California JA8 certified.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

## Performance:

|                        |   |
|------------------------|---|
| Number of Modules      | 1   |
| Input Power            | 28.3w   |
| Input Voltage          | 120-277 V   |
| Input Frequency        | 60 Hz   |
| Lumens/LPW (Delivered) | 1660/59.5 (LM-79)   |
| CCT                    | 3000 K  |
| CRI                    | 90 CRI  |
| Life (hours)           | 58,000 (L70/TM-21)  |
| FCC                    | FCC Title 47, Part 15, Class A  |
| Min. Start Temp        | -30 °C  |
| Max. Operating Temp    | 30°C  |
| Warranty               | 5 year limited warranty   |
| Labels                 | cETLus Damp location listed<br>ENERGY STAR® qualified<br>Meets California Title 24 JA8-2016 |

## P350070-009-30

## Images:



## Dimensions:

Diameter: 15"  
Height: 3-11/16"

Glass  
Width: 12-3/4"  
Height: 2-1/8"

**P350070-009-30****Dimming Notes:**

---

P350070 is designed to be compatible with many 0-10V controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron - NFTV

Lutron - NTFTV

Lutron - DDTV

Leviton - AWSMT-7DW

Leviton - IP710

Lithonia ISD BC

Pass & Seymour - CD4FB

Wattstopper ADF-120277

Hunt Dimming - PS-010-120V

Hunt Dimming - PS010 277V

Lightolier Controls - MP1500FAM120

Lightolier Controls - ZP600FAM120

Synergy Lighting Controls - V2000FAMU

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.