

| Project:      |  |  |
|---------------|--|--|
| Fixture Type: |  |  |
| Location:     |  |  |
| Contact:      |  |  |

# Wall Lantern

Wall mounted • Wet location listed PROGRESS LED





## **Description:**

Inspired by traditional lantern styles, Whitacre incorporates handsome details. Clear seeded glass surrounds an etched opal glass candle diffuser. An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.

## **Specifications:**

- Antique Bronze (-020) (painted)
- Aluminum construction
- Clear Seeded with Etched Ivory diffuser Glass globe
- · Inspired by traditional lantern styles, Whitacre incorporates handsome details
- · An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.
- Clear seeded glass surrounds an etched opal glass candle diffuser
- Includes one 9-watt replaceable LED modulesWarm white, 3000K, color temperature, 90 CRI
- 624 lumens, 66 lumens per watt (source)
- Wall lantern adds illumination to walkways and pathways to enhance safety and security
- Replaceable light engine is California JA8 certified
- Can also be used in interior settings and paired with decorative fixtures for creative design ideas.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016

#### **Performance:**

| Number of Modules      | 1                                   |  |
|------------------------|-------------------------------------|--|
| Input Power            | 9w                                  |  |
| Input Voltage          | 120 V                               |  |
| Input Frequency        | 60 Hz                               |  |
| Lumens/LPW (Source)    | 624/66 (LM-82)                      |  |
| Lumens/LPW (Delivered) | 351/37.7 (LM-79)                    |  |
| CCT                    | 3000 K                              |  |
| CRI                    | 90 CRI                              |  |
| Life (hours)           | 60,000 (L70/TM-21)                  |  |
| FCC                    | Meets FCC Title 47, Part 15 Class B |  |
| Min. Start Temp        | -30 °C                              |  |
| Max. Operating Temp    | 30°C                                |  |
| Warranty               | 5 year limited warranty             |  |
| Labels                 | cCSAus Wet location listed          |  |
|                        | ENERGY STAR® qualified              |  |
|                        | Meets California Title 24 JA8-2016  |  |

# P560069-020-30

#### Images:



#### **Dimensions:**

Width: 10" Depth: 10" Height: 18" H/CTR: 4"

Glass Width: 6-1/2" Height: 10-1/2" Glass 2 Width: 3-5/8" Length: 3-5/8" Height: 3-5/8"



# Wall Lantern



# P560069-020-30

### **Dimming Notes:**

P560069 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.