

SMYRNA

 Ceiling mounted • Wet location listed **PROGRESS LED**

P2576-2030K

Description:

This 52" Smyrna ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. The light kit contains a clear hammered glass shade and contains a 17W dimmable 3000K LED module. The five-blade fan features a dual mount system and has an all weather wet location rating (ABS) to accommodate a variety of settings inside and outside of the home. Smyrna is available in two finish options: Antique Bronze and Forged Black. Can be used to comply with California Title 20.

Specifications:

- Antique Bronze (-20) (Painted)
- Steel construction
- Clear hammered glass Diffuser
- The light kit contains a clear hammered glass shade and contains a 17W dimmable 3000K LED module with 90CRI and 1400 lumens
- A wall switch is included
- The five-blade Smyrna fan features a dual mount system and has an all weather wet location rating (ABS blades) to accommodate a variety of settings inside and outside of the home
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ideal for Traditional exteriors
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- UL Wet location listed for wet locations
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately
- Can be used to comply with California Title 20.
- High Speed Energy Information: Airflow- 4585 cfm, Energy consumption- 58 watts (excluding lights), Airflow efficiency- 79 cfm/watt
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Walnut blades, plastic construction
- 12 degree blade pitch
- Wall Control Included
- Meets California Title 24 JA8-2016

Performance:

| | |
|---------------------|------------------------------------|
| Number of Modules | 1 |
| Input Power | 18w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW | 1386/77 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50,000 (L70/TM-21) |
| EMI/RFI | Title 20 |
| Min. Start Temp | -10 °C |
| Max. Operating Temp | 40 °C |
| Warranty | Limited Lifetime warranty |
| Labels | UL Wet location listed |
| | Meets California Title 24 JA8-2016 |

Images:



Dimensions:

Diameter: 52"
Height: 19-1/2"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$10

\$3\$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 36 Watts

Airflow

3,267

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 91 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights

ftc.gov/energy

P2576-2030K

Dimming Notes:

P2576 is designed to be compatible with many controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

"Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron - Caseta Wireless

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW"

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.