

Project:

Fixture Type:

Location:

Edwidge

Ceiling Mounted • Damp Location Listed PROGRESS LED

Contact:

Description:

Edwidge Collection 3-Blade Black 52-Inch DC Motor LED Contemporary Ceiling Fan

Specifications:

- · Frosted Acrylic Bowl
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5.75 in W., 2.25 in ht., 5.75 in depth
- 80 in of wire supplied

Performance:

Number of Modules	1
Input Power	18 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,400
ССТ	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	Limited Lifetime Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016
	DC motor

P250062-031-30



Dimensions:

Length: 52 in Diameter: 52 in Height: 13-1/2 in

Frosted Acrylic Bowl Width: 7-1/2 in Height: 2-1/2 in



Edwidge

Ceiling Mounted · Damp Location Listed PROGRESS LED

Dimming Notes:

P250062-031-30

P250062-031-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Eaton AAL06 IDevices IDEV009 Leviton 6681 Leviton 6672 Leviton 6674 Lutron NTEVL-300 Lutron DVELV-300P Lutron DVCL-253P Lutron AYCL-153P Lutron SCL-153P Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.